



AQUABREAK PX 25 LTR

Product group: **651** Product number: **575613**

Unitor™ Aquabreak PX™ is a multipurpose cleaning and degreasing agent. It is low-toxic, non-caustic, free of hydrocarbon solvents and biodegradable.



Product information

Unitor™ Aquabreak PX™ removes effectively dirt and oily matters without the use of solvents and caustic based cleaners.

The surfactant formulation with complex binders has an excellent cleaning efficiency.

Unitor™ Aquabreak PX™ is NSF approved so it can be used to clean food serving areas and food stations.

Optimal for use in the following applications:

- Good for use in galleys and on decks
- Engine room cleaner
- Suitable for cargo tank cleaning
- Suitable for cleaning of soiled textiles as rugs, covers, mats, overalls etc.
- Effectively cleans fiberglass boats

Features

- Multi purpose water based degreaser
- Highly concentrated
- Biodegradable, low toxic and non-caustic
- Safe on all materials

Benefits

- Has several applications so you can minimise the number of cleaners used onboard
- Safe to use and your safety is always our priority
- Minimise the risk to damage surfaces

Specification

General

Invent Hazard Material (IMO/EU) classification	C-49
---	------

Physical properties

Appearance	Pale yellow
Density [g/ml]	1,0
Form	Liquid
pH	12

Approvals

Approved by NSF

Nordic Swan eco-labelled.

This composition meets the criteria for not being harmful to the marine environment according to MARPOL Annex V and may be discharged into the sea when used to clean cargo holds and external surfaces on ships.

IMO approved and listed in Annex 10 of the MEPC.2/ Circular

Approved by Marinfloc AB for use in engine rooms

[Aquabreak-approval-drink-water-offshore](#)

Directions for use

General Cleaning

Unitor™ Aquabreak PX™ can be used for all types of cleaning and degreasing, and it can be applied by brush, hand spray or used in ultrasonic bath.

It is recommended to test different concentrations on a small area to find the optimal effect on the contaminated surface. Depending on the amount and type soil to be removed, common dosage for light contamination is about 1-5%, for heavy contamination up to 20%.

For safe handling and optimal dilution we recommend the use of the UNITOR™ MIXING STATION 4-14.

Unitor™ Aquabreak PX™ can be applied on vertical surfaces by adding Unitor™ Foam Agent™ for increasing the resident time.

Tank Cleaning

Direct injection method with tank washing machines:

Use a dose rate of 0.5-5 litres per ton wash water (0.05-0.5%).

Recirculation method:

Use a dose rate of 0.5-7 litres per ton wash water (0.05-0.7%).

Spot cleaning: Hand sprayed neat or diluted up to 1-5 parts with water. Leave solution for about 20-30 minutes before washing off, but make sure the surface remains wet.

For problem deposits, please consult the Unitor™ Tank Cleaning Manual.

Unitor™ Aquabreak PX™ can be used on the majority of tank coating materials, painted or lacquered surfaces, light metals, plastics and textiles.

Related products

Accessories

614537 FOAM - AGENT 3X5 LTR

Is accessory to

778955	UNITOR CARGO HOLD COMPACT KIT	766899	ULTRASONIC CLEANER S-700/HM, 110V
766956	ULTRASONIC CLEANER S-3300/HM, 440V	766923	ULTRASONIC CLEANER S-2000/HM 230V
766907	ULTRASONIC CLEANER S-1600/HM 230V	766881	ULTRASONIC CLEANER S-700/HM, 230V
778914	OILSPILL MARPOL KIT 7 BARREL(2 PALLETS)	778922	OILSPILL MARPOL KIT1 BARREL(1 PALLET)
778855	PANAMAX CARGO HOLD CLEANING KIT	778993	OILSPILL MARPOL KIT 12 BARREL(2 PALLETS)

Is frequently bought together with

589945	GAMAZYME BTC 12 X 1 LTR	765018	ENVIROCLEAN 25 LTR
571364	VAPTREAT 25LTR	698720	AUTOTREAT - 25 LTR
571356	ROCOR NB LIQUID 25 LTR		

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/cleaning-and-maintenance/aquabreak-px-25-ltr/>